



NTN Bearing Driveshaft do Brasil



0.984 Inch | 25 Millimeter x 2.441 Inch | 62
 Millimeter x 1 Inch | 25.4 Millimeter SKF 3305
 A-2RS1TN9/W64 Angular Contact Ball Bearings

Bearing No. 3305 A-2RS1TN9/W64

3305 A-2RS1TN9/W64 Bearing 2D drawings and 3D
 CAD models

Category	Angular Contact Ball Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	0
EAN	7316571452401
Product Group	B00152
Enclosure	2 Seals
Flush Ground	No
Rolling Element	Ball Bearing
Number of Rows of Balls	Double Row
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Polyamide
Contact Angle	30 Degree
Internal Clearance	C0-Medium
Number of Bearings	1 (Single)
Inch - Metric	Metric
Long Description	25MM Bore; 62MM Outside Diameter; 25.4MM Width; 2 Seals; No Flush Ground; Ball Bearing; Double Row of Balls; ABEC 1 ISO P0; No Filling Slot;



NTN Bearing Driveshaft do Brasil

	No Snap Ring; C0-Medium; Polyamide Cage; 30 Degree; 1 (Si
Other Features	NBR Contact Seal Glass Fibre Reinforced Cage W64-Standard Synthetic Grease
Category	Angular Contact Ball Bearing
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	3305 A-2RS1TN9/W64
Weight / LBS	0.7936
D	2.441 Inch 62 Millimeter
B	1 Inch 25.4 Millimeter
d	0.984 Inch 25 Millimeter
bore diameter:	25 mm
snap ring included:	Without Snap Ring
outside diameter:	62 mm
bearing material:	Chrome Steel
overall width:	1.0000 in
radial dynamic load capacity:	7194 lbf
contact angle:	30 °
radial static load capacity:	4586 lbf
row type & fill slot:	Double-Row Non-Fill Slot
operating temperature range:	0 ° F to 185 ° F
internal clearance:	C0
cage material:	Steel
bore type:	Round
finish/coating:	Uncoated



NTN Bearing Driveshaft do Brasil

closure type:	Double Seal
application:	Metal manufacturing, Paper mills, Steel mills – plate, slab, strip, blast furnace, Overhead cranes, Food and beverage, Rock and stone conveyors, Shipyards Metal manufacturing Pap